

Kunlun GL-5 Super Automotive Gear Oil

Kunlun GL-5 Super Automotive Gear Oil is an extreme pressure gear lubricant specially formulated for 'Limited Slip' rear drive differentials, especially 'Cone Clutch' design. The excellent friction properties provide smooth, noise free operation and extended life of these units.

Performance Standards

Kunlun GL-5 Super Automotive Gear Oil meets the following performance requirements:

- API GL-5
- API MT-1

Benefits

Kunlun GL-5 Super Automotive Gear Oil provides the following benefits:

- Provides superior lubricity characteristic for smooth, non-stick / slip engagement and disengagement of friction elements.
- Ensures a continuous lubricant film on gears operating under the severest conditions involving heavy dynamic and shock loads and very high or intermittent sliding speeds between the teeth.
- Maintains outstanding anti-wear properties and reduces gear-tooth and bearing wear.
- Provides excellent thermal stability and anti-corrosion properties.
- Maximizes anti-rust properties and effectively prevent rust on gears and in bearings.

Typical Characteristics

Kunlun GL-5 Super Automotive Gear Oil

SAE Grade	S0W-90	SSW-140
Kinematic Viscosity		
40°C, mm ² /s	158.1	383.9
100°C, mm ² /s	15.4	28.1
Viscosity Index	104	100
Specific Gravity, 15°C, g/cm ³	0.894	0.907
Flash Point, COC, °C	215	226
Pour Point, °C	-27	-21